

**CEL459: River Mechanics**  
**Minor I**

Marks: 20

Time: One Hour

Solve the following. Assume the missing data suitably.

Q.1 (a) Describe different flow regimes in slurry flow through a pipeline. [2]

(b) Describe the basic slurry pipeline transportation system. [2]

Q.2 Derive the equation for sediment concentration profile considering particle diffusivity  $\epsilon$  as (a) constant (b) variable.

[4]

Q.3 Plot shear stress vs. shear rate curves for different type of fluids: [4]

Q.4 Determine the type of flow and the pressure drop per meter of pipe length for the following data:

Flow Rate (Q)	m <sup>3</sup> /hr	800
Pipe Inside Diameter (D)	mm	250
Bingham Yield Stress ( $\tau_{YB}$ )	Pa	6.0
Plastic viscosity ( $\eta_P$ )	Pa.s	0.03
Slurry Density ( $\rho$ )	kg/m <sup>3</sup>	1250
Wall Shear Stress ( $\tau_w$ )	Pa	9.0

[4]

Q.5 Derive the expression for discharge in laminar flow of Herschel-Bulkley fluid through pipeline.

[4]

*Bingham Plastic – Laminar Friction Factor:*

$$R_{BP} = \frac{DV\rho}{\eta_P} \text{ and } He = \frac{D^2\tau_{YB}\rho}{\eta_P^2} \text{ and } f_L = \frac{16}{R_{BP}} \left[ 1 + \frac{He}{6R_{BP}} + \frac{He^4}{3f_f^3 R_{BP}^7} \right]$$

*Bingham Plastic – Turbulent Friction Factor:*

$$f_{\pi} = 10^a R_{BP}^b \text{ where } a = -1.47 \left[ 1 + 0.146 \exp(-2.9 \times 10^{-5} He) \right] \text{ and } b = -0.193$$

*Bingham Plastic – Combined Friction Factor:*

$$f_f = (f_L^m + f_{\pi}^m)^{1/m} \text{ where } m = 1.7 + \frac{40000}{R_{BP}}$$

Hints:

$$\frac{8\rho V_{ann}^2}{\tau_{TH} + K \left( \frac{8V_{ann}}{D_{shear}} \right)^n} ; \pi R^3 n \left( \frac{\tau_w}{K} \right)^{1/n} (1-\phi)^{(n+1)/n} \left\{ \frac{(1-\phi)^2}{3n+1} + \frac{2\phi(1-\phi)}{2n+1} + \frac{\phi^2}{n+1} \right\}$$

$$\frac{nR}{(n+1)} \left( \frac{\tau_w}{K} \right)^{1/n} (1-\phi)^{(n+1)/n}$$